

# TECHNICAL DATA SHEET



## **1. Product Name**

*WOOD IRON INTERIOR MODIFIED URETHANE TOP COAT FINISH  
– SATIN AND SEMI-GLOSS*

## **2. Manufacturer**

Wood Iron Wood Finishes, Inc.  
10475 Irma Drive, Unit 7  
Northglenn, CO 80233-4227

## **3. Product Description**

WOOD IRON INTERIOR TOP COAT is a clear finish for new interior wood surfaces. The Satin leaves a fairly flat finish with a slight sheen. The Semi-Gloss leaves a shinier, reflective sheen. The Top Coat will stay clear and dries quickly so successive coats can be done in one day. It will not yellow like lacquer or varnish and has a urethane component that makes it tough and durable. It is low odor, low V.O.C., non-combustible and non-flammable.

**Basic Use:** It is designed for use interior new wood that is stained or unstained. It can be used on doors, trim, window frames, window seats and wood furniture for interior use.

**Composition and materials:** WOOD IRON INTERIOR TOP COAT FINISH is a water-based acrylic finish with modified urethane.

## **4. Installation**

All interior wood to be finished must be free of dirt and other surface contaminants. Do Not assume that new wood is free of contamination. All interior wood to be finished must be free of dirt, marks, fingerprints and other surface contaminants. Do Not assume that new wood is free of contamination. All interior new wood must be cleaned before coating.

### **Cleaning/Preparation**

1. Sand with open coat, non-stearated sand paper 150 grit combined with a random orbital sander or use a medium/fine sanding sponge.
2. Sand with the grain.
3. Remove dust by duster brush and/or compressed air. Do not use tack clothes.

Note: Wood will develop a "patina" that when sanded through will reveal a lighter color substrate. If sanding is the preparation of choice, be prepared to sand everything to produce an even looking surface.

**CAUTION:** Do not use steel wool. Particles that might remain on the surface can rust.

For the cleaning and preparation of the interior of a log home or wood walls or ceilings please ask for our Section 9900 Specification for Interior Finishing.

## **Application**

Wood must be completely dry and free of blemishes and surface contamination.

Mask all items not receiving finish such as windows, floors, carpet, etc.

*Note: Check all areas before applying finish. Wood should be free of splinters, dust, oil or any other unevenness or contamination.,*

Follow all directions on the label at all times.

## **5. Availability and Cost**

**Availability:** WOOD IRON INTERIOR TOP COAT FINISH is available from dealers in the Western United States. Call 1-888-966-3476 for the closest dealer.

**Cost:** Cost is available from dealers or from the National Distributor at 1-888-966-3476.

## **6. Warranty**

Limited Warranty: Satisfaction is warranted with the application, appearance and performance properties of this product if it is applied correctly in accordance with label directions and at the designated spread rate. Wood Iron Wood Finishes, Inc., makes no other express warranties, in the event the product fails to conform to this warranty. Wood Iron Wood Finishes, Inc. as its sole liability and in lieu of any direct or indirect, incidental, special or consequential damages, will, at your choice, furnish replacement product or refund the purchase price. Labor or costs of labor for the application of any product specifically are excluded. You must supply proof of purchase. This warranty gives you specific legal rights and you may have other rights which vary from state to state. To make a claim under this warranty contact the distributor from whom you purchased the product.

## **7. Technical Services**

Support for technical and other issues can be obtained from Wood Iron Wood Finishes, Inc. in Northglenn, Colorado at (303) 650-1681 or 1-888-966-3476.